5.4V 7.5F 2 SERIAL MODULE

VINA Tech

FEATURES

2 units serially connected to provide 5.4V products

Lead terminal type

2-Pin terminal type according to customer's requirement



Drawing

I TYPE



O TYPE



H TYPE



D = 13mm

TYPE	I	O	H
P	7.5	18.5	13

SPECIFICATION

ITEM		CHARACTERISTICS
Rated Voltage (V_R)		5.4 V
Operating Temperature		-40 ~ +65℃
Capacitance Tolerance		-10 ~ +30%
High Temp. Load Life (65℃)	Measure	After 1,000 hours at V_R loaded under +65℃, capacitors meet the following criteria.
	Cap. Change	≤ 30% of initial value
	ESR Change	100% increase from specified value
Cycle Life Characteristics	Cycle	500,000
	Cap. Change	≤ 30% of initial value
	ESR Change	100% increase from specified value
	Condition	Cycle of Charge/discharge from V_R to $1/2V_R$
Shelf Life		2 years No Electrical Charge, Temperature Below 70℃ (ΔC : ≤10% of initial value / ΔESR : ≤ 50% of initial value)

Part Number	Rated Voltage (V)	Capacitance (F)	ESR (mΩ)		Max. Current (A)	Leakage Current (㎃, 72hr)	Size (㎜)	Weight (g)	Volume (㎖)
			AC(1㎑)	DC			D × W × L		
VEC5R4755QG	5.4	7.5	55	85	12.5	0.030	13×26×28	9.6	9.5

*** Max. Current** : 1 sec. discharge to $1/2V_R$

*** When do module more than 2 series, please fully discharge over 1 hour first, then assemble right after within 1 hour.**

Vina Tech Co., Ltd. **Tel : +82 31 448 3066** **E-mail : hycap@vina.co.kr** **Web : www.vina.co.kr**